

VT210 - NEW

COMPACT LOADERS



Key Features

- ✓ Color Display with Keyless Start + Security Code
- ✓ IdealTrax™ Auto Tensioning System
- ✓ Lift Arm Shape to Reduce Material Build-Up on Arms + Improve Visibility
- ✓ Auxiliary Hydraulics with Drain Case
- ✓ LED Work, LED Rear Lights + Egress Lighting
- ✓ Vertical Lift Arm for more Reach at Dump Height
- ✓ Hydraglide™ Ride Control
- ✓ Dual Flange Idlers - Front + Rear
- ✓ Pilot Joystick Controls
- ✓ Backup Alarm

Key Specifications

- ✓ Operating Capacity (35%) - 952 kg (2,100 lbs.)
- ✓ Overall height to top of ROPS - 2045 mm (80.5")
- ✓ Gross Power - 51.7 kW (69.3 hp)
- ✓ 241 Nm (178 ft.-lbs.) @ 1625 rpm max torque
- ✓ 3073 mm (121") height to hinge pin
- ✓ 1674 mm (65.9") machine width - less bucket
- ✓ 4021 kg (8,865 lbs.) operating weight

SPECIFICATIONS

		METRIC
Capacities	Operating Weight	4021 kg
	Unladen weight	3651 kg
	Operating Capacity at 35% Tipping Load	952.54 kg
	Operating Capacity At 50% Tipping Load	1360.77 kg
	Tipping capacity	2721 kg
Weight and dimensions	Overall Operating Height - Fully Raised	4026 mm
	Height to Hinge Pin - Fully Raised	3073 mm
	Dump reach - Full height	927 mm
	Dump angle at full height	42 °
	Overall Height to top of ROPS	2045 mm
	Overall length with bucket	3543 mm
	Ground clearance	191 mm
	Overall width less bucket	1674 mm
	Clearance Radius - Front with Bucket	2210 mm
Engine	Engine brand	Yanmar
	Engine model	4TNV98C-NGL
	Gross Power	51.70 kW
	Net Power	51 kW
	Max. torque / Engine rotation	241 Nm @ 1625 rpm
	Battery voltage	12 V
Hydraulics	Alternator - Ampere	100 A
	Standard flow - Auxiliary hydraulics	86.50 l/min
	Auxiliary Hydraulic Pressure	239.59 bar
	High-Flow Auxiliary Hydraulics - Option	114 l/min
Tank capacities	High-Flow Auxiliary Hydraulics Pressure - Option	229.25 bar
	Hydraulic tank capacity	22.70 l
	Fuel tank	143.80 l
	Displacement / Number of cylinders	3.30 l / 4



STANDARD FEATURES

- 4 point lift
- Rear Lights
- Anti-Vandalism Protection
- Auxiliary Hydraulics
- Hydrostatic Drive - Servo
- Hydraloc™ Safety System
- Sound reduction Package
- Back-Up Alarm
- Brake Control (Auto / Manual)
- Engine Block Heater
- 12Volt Power Port
- IdealTrax™ Automatic Track Tensioning System
- LED Work Lights
- Horn
- Single Flange Front/Dual Flange Rear Idlers
- Hand throttle
- Two-Speed Drive
- Cup Holder
- Engine Auto-Shutdown System
- Hydraglide™ Ride Control

OPTIONAL FEATURES

- Counterweight
- A/C Cabin
- Rearview Camera
- Power-A-Tach® Attachment Mounting System
- Suspension Seat - Mechanical
- Selectable Self-Leveling Hydraulic Lift Action
- Cab Enclosure
- Inner rear view mirror
- ROPS/FOPS Level II Overhead Guard
- Suspension Seat - Air Ride

Manitou Group reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. Manitou Group reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT